

IP CCTV / Professional IP cameras / Uniview - Uniarch / Bullet Cameras

UV-IPC-B122-APF28-ECO

UNIARCH



Features

- Bullet IP camera
- 2 Megapixel (1920x1080)
- 2.8 mm Lens
- Minimum illumination 0.02 Lux | 0 Lux with supplemental lighting
- IR Range 30 m
- DWDR
- PoE IEEE802.3af
- Weatherproof IP67
- Built-in microphone
- ONVIF compatible

Specifications

Range	Uniarch
Image sensor	1/2.9" Progressive Scan CMOS
Maximum resolution	2 Megapixel (1920x1080)
Main Stream rate	1080P (1920*1080), Máx 25fps; 720P (1280*720), Máx 25fps
Extra Stream rate	D1 (720*576), Máx 25fps; 640*360, Máx 25fps; 2CIF(704*288), Máx 25fps; CIF(352*288), Máx 25fps
Compression	Ultra265/H.265/H.264
Lens	2.8 mm
DORI Distance	Detect: 45 m Observe: 18 m Recognize: 9 m Identify: 4.5 m
Opening angle	Horizontal: 101.1 ° Vertical: 55 ° Diagonal: 111 °
Minimum illumination	0.02 Lux (Colour) 0 Lux with IR
Infrared range	30 m
Image improvements	DWDR, AGC, 2D/3D-DNR, ROI, Privacy Mask, Smart IR
Day / Night	Mechanical ICR filter
Internal memory	Does not have
Alarms	Does not have
Audio	Built-in microphone
Network interface	Ethernet 10/100 BaseT
Remote access	Web Browser, CMS Software (EZStation), Smartphone (EZView/EZLive)
Interoperability	ONVIF
Power supply	DC 12 V / 3.5 W, PoE IEEE802.3af
Temp. operation	-30° C ~ 60° C
Degree of protection	Weatherproof IP67
Dimensions	65 (H) x 62 (W) x 160 (D) mm

Weight

210 g
